

Bandsaw Basa 3.0v

No other bandsaw offers as much as the scheppach Basa 3.0v. Equipped with special feature of variable speed setting from 370 to 750 rpm this machine is perfect for cutting a variety of materials. Check and compare the Basa 3.0v specification with our competitors and you will immediately recognise how much more you get with this economically priced bandsaw. Without question it offers the best performance/specification – to price - ratio. Scheppach Basa 3.0v: in a class of its own.

Vario drive
Unique; 370 to 750 rpm




Unique vario drive, continuously adjustable by hand wheel.



Impressive passage height of 205 mm, and passage width of 306 mm.



Quick-clamping system for quick changing of bandsaw blade.



Simple continuous table setting from -8° to +45°.



The Basato 3.0 with optional equipment: Base bench with wheel assembly.



Table inclination setting by hand wheel, possible with one hand.



Tempered 3-roller precision guiding above and under the table.



Cutting height adjustment by hand wheel.



Precision ripping fence with magnifying glass, to be inserted from above.

scheppach features

- Unique vario drive adjustable from 370 to 750 rpm
- Sturdy cast-iron table tilting from -8° to +45°
- 3-roller precision guiding above and below the table
- Balanced and polished band wheels with rubber facing
- Upper saw blade guiding by toothed rack, adjustable for height
- Quick-clamping lever for saw blade

Cutting data

- Passage height 205 mm
- Passage width 306 mm

Standard equipment

- Precision ripping fence with magnifying glass, to be used at left and right side of saw blade
- Phase inverter (400V)

Technical Data

- Table size 548 x 400 mm
- Table height 520 mm
- Band wheel \varnothing 315 mm
- Saw blade length 2360 mm
- Saw blade width min. 3,0 to max. 15 mm
- Certificates CE, tested for wood dust
- Suction connection piece \varnothing 100
- Dimensions: L 860 x W 600 x H 1115 mm
- Weight approx. 69,0 kg

Accessories

Bandsaw blades see [page 58](#)



Base unit with wheel assembly
Working height 1050 mm
Order no. **1901503701**

Cross-cutting gauge
Order no. **73120025**

Professional accessory pack
consisting of:
1 circle-cutting device
for 6 mm saw blades radius min. 35 mm, max. 265 mm,
and
1 depth stop
continuous setting of cutting depth from 0 to 200 mm for slots and tenons,
and
1 sanding belt attachment
sanding belt grit 60
Order no. **73190710**

Set of sanding belts
3 pieces each
grit 60
Order no. **73190711**
grit 120
Order no. **73190712**



Illustration shows optional equipment available at extra cost.

Order information Basa 3.0v

Motor equipment V/Hz	220-240/50	400/50
Input kW (hp)	0,8 (1,1)	0,7 (1,0)
Order no.	1901503901	1901503902