

FX 12/4 GH

THREE-PHASE POWER GENERATOR / OUTPUT POWERGRUPPO **11 KVA** THREE-PHASE AND **4 KVA** SINGLE-PHASE / PETROL ENGINE **3000 RPM**

Gen Set Features	+ Low oil level cut out device + 12 V built-in battery with electric start + 1 x 16 A, 400 V - 50 Hz three-phase EEC socket protected by circuit breaker + 1 x 16 A, 230 V - 50 Hz single-phase EEC socket protected by circuit breaker + Earth Leakage Circuit Breaker (ELCB) + Voltmeter + Hourmeter + Central lifting eye	
Gen Set Options (available as factory options)	+ Version with different voltages + 60 Hz version + AMF/ATS panel for auto start operation	
Accessories on Request	+ Trolley	two-wheels and handles
Noise Level	+ Lwa 98	(73 dB a 7 m)
AC Generator 50 Hz	+ Type synchronous + Three-phase p. (stand-by) 11 kVA - 400 V + Three-phase p. (prime) 10 kVA - 400 V + Single-phase p.r (max.) 4 kVA - 230 V + Power Factor 0,8	
Petrol Engine 3000 rpm	+ Type Honda GX 630 OHV - 2 cil. 14,1 CV (10,5 kWm) - 688 cm3 + Fuel Petrol + Cooling system air + Starting system electric + Fuel tank capacity 29 l + Fuel consumption @ 75% 6 l/h (@ 3600 rpm)	
Other features	+ Insulation Class H + Ambient temperature 40 °C + Altitude 1000 mt + Mechanical Protection IP 23 + Dimensions (L x W x H) 940 x 488 x 823 mm + Dry weight 148 kg	

FX 12/4 GH



mase
GENERATORS